

WAAS CH 53410 W10A	APP CRS 104°	Rwy Ldg TDZE Apt Elev	9490 6591 6606
--	------------------------	-----------------------------	---

RNAV (GPS) Y RWY 10
YAMPA VALLEY (HDN)


RNP APCH-GPS.

⚠ Rwy 10 helicopter visibility reduction below ¾ SM NA.
Inop table does not apply to *LPV all Cats, LNAV/VNAV all Cats, and LNAV Cats C/D. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -28°C or above 54°C.

MALSF

⚠ MISSED APPROACH: Climb to 13700 direct OBTUE and on track 124° to TILLI and hold, continue climb-in-hold to 13700.
* Missed approach requires minimum climb of 295 feet per NM to 8700.

AWOS-3 119.275	DENVER CENTER 120.475 235.975	UNICOM 123.0 (CTAF)
--------------------------	---	-------------------------------



ELEV 6606	D	TDZE 6591
-----------	----------	-----------

7 NM Holding Pattern

14000 ← 284°
10000 → 104°

GP 3.00°
TCH 55

104°

6639

0.3% DOWN

10000 X 150

REIL Rwy 28

HIRL Rwy 10-28

	REVME	INDE	13700	OBTUE	tr 124°	TILLI
	7 NM Holding Pattern	8700	3.5 NM to RWY 10			
	104°	104°				
	6.8 NM	3 NM	3.5 NM			
CATEGORY	A	B	C	D		
LPV DA*	6791-¾ 200 (200-¾)					
LPV DA	7327-1¾ 736 (800-1¾)					
LNAV/VNAV DA	7966-5 1375 (1400-5)					
LNAV MDA	7760-1 1169 (1200-1)	7760-1¼ 1169 (1200-1¼)	7760-3	1169 (1200-3)		
CIRCLING	7760-1¼ 1154 (1200-1¼)	7760-1½ 1154 (1200-1½)	7760-3	8180-3 1574 (1600-3)		

SW-1, 04 SEP 2025 to 02 OCT 2025

SW-1, 04 SEP 2025 to 02 OCT 2025