

WAAS
CH **56221**
W33A

APP CRS
331°

Rwy Idg
TDZE
Apt Elev

5500
217
236

RNAV (GPS) RWY 33

RICHMOND EXEC/CHESTERFIELD COUNTY (F'CI)

▼

▲ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). When local altimeter setting not received, use Richmond Intl altimeter setting; increase LPV DA to 546 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 634 feet and all visibilities ½ SM; increase all MDAs 40 feet and LNAV visibility Cat C/D ½ SM and Circling visibility Cat D ½ SM. DME/DME RNP-0.3 NA. For inop MALSR, increase LPV all Cats visibility to 1 mile and LNAV Cat C/D to 1½ mile. For inop MALSR when using Richmond Intl altimeter setting, increase LPV all Cats visibility to 1 ½ mile. Baro-VNAV and VDP NA when using Richmond Intl altimeter setting.

MALSR

MISSED APPROACH:
Climb to 3000 direct
DOCEV and hold.

AWOS-3PT
128.625

POTOMAC APP CON
126.75 307.2

CLNC DEL
124.6

UNICOM
123.05 (CTAF) 0

MISSED APCH FIX

ELEV 236

TDZE 217

3000		DOCEV	*LNAV only	4 NM Holding Pattern			
		PUBBS 2000	SALPE				
RW33		*1.5 NM to RW33	2000	GP 3.00° TCH 49			
1.5		3.9 NM	6 NM				
CATEGORY	A	B	C	D			
LPV DA	510-½		293 (300-½)				
LNAV/VNAV DA	598-⅞		381 (400-⅞)				
LNAV MDA	720-½ 503 (500-½)		720-1 503 (500-1)				
CIRCLING	720-1 484 (500-1)	760-1 524 (600-1)	760-1½ 524 (600-1½)	1020-2½ 784 (800-2½)			

RICHMOND, VIRGINIA

Orig-E 02DEC21

RICHMOND EXEC/CHESTERFIELD COUNTY (F'CI)

37°24'N - 77°31'W

RNAV (GPS) RWY 33