

VORTAC STL	APP CRS	Rwy Idg	3800
117.4	208°	TDZE	437
Chan 121		Apt Elev	437



VOR RWY 18

ST CHARLES COUNTY RGNL/SMARTT FLD (SE/T)

⚠ When local altimeter setting not received, use St Louis Lambert Intl altimeter setting and increase all MDAs 60 feet and Circling visibility Cat C ¼ SM. NUPDE fix minimums: increase Circling visibility Cat C ¼ SM. Straight-in minimums NA with St Louis Lambert Intl altimeter setting.

MISSED APPROACH: Climb to 1000 then climbing left turn to 2700 via heading 360° and STL R-031 to FASHE INT/19.4 DME and hold.

ASOS 118.075	ST. LOUIS APP CON 124.2 353.9	CLNC DEL 121.6	UNICOM 122.7 (CTAF) 0
-----------------	----------------------------------	-------------------	--------------------------



ELEV 437	TDZE 437	1000	2700	STL R-031	FASHE	BYRNS INT STL 10	Remain within 10 NM
208°	hdg 360°	STL 5	STL 6	NUPDE STL 6.7	2300	208°	2300
VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 40).							
NUPDE FIX MINIMUMS							
S-18							
CIRCLING							
S-18							
CIRCLING							