

APP CRS
188°

Rwy Idg
TDZE
Apt Elev

3501
1204
1207

RNAV (GPS) RWY 19

ASHLAND COUNTY (3G4)

RNP APCH.

▼

NA

Rwy 19 helicopter visibility reduction below 1 SM NA.
Procedure NA at night. Use Mansfield altimeter setting,
when not received use Wooster altimeter setting.

MFD ASOS
125.3

CLEVELAND APP CON ★
128.35 360.65

UNICOM
122.7 (CTAF)

The chart displays the RNAV (GPS) RWY 19 approach. Key features include:

- Waypoints:** CIDUX (IAF), ECZIF (IF/IAF), FEVEV (IAF), JUKAP (FAF), HINPO, and READS.
- Altitudes:** 1949 A, 3000, 2800, 2880, 1299±, 1276±, 1609, 1725.
- Distances:** 4 NM, 30 NM, 1.5 NM, 0.8 NM, 0.5 NM, 4.9 NM, 6.1 NM.
- Angles:** 098°, 278°, 008°, 188°, 285°, 105°.
- Obstacles:** 1609, 1725.
- Procedures:** MISSED APPROACH: Climb to 3000 direct HINPO and left turn on track 098° to READS and hold.

ELEV 1207

TDZE 1204

188°

61

0.5% UP

3501 X 7.5

3000

HINPO

tr 098°

READS

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 20).

4 NM Holding Pattern

JUKAP

3.04° TCH 40

188°

008°

3000

2800

4.9 NM

6.1 NM

CATEGORY	A	B	C	D
LNAV MDA	1600-1	396 (400-1)	1600-1 ¹ / ₈ 396 (400-1 ¹ / ₈)	NA
CIRCLING	1660-1	453 (500-1)	1740-1 ¹ / ₂ 533 (600-1 ¹ / ₂)	NA

ASHLAND, OHIO

Orig-F 09SEP21

40°54'N-82°15'W

ASHLAND COUNTY (3G4)

RNAV (GPS) RWY 19