



WAAS CH 86231 W16A	APP CRS 156°	Rwy Idg TDZE 1459 Apt Elev 1478
--	------------------------	---

RNAV (GPS) RWY 16

TAYLOR COUNTY (MDZ)

RNP APCH.	When local altimeter setting not received, use Merrill altimeter setting and increase all MDA 100 feet and increase all Cat C/D visibility ¼ mile. Rwy 16 helicopter visibility reduction below ¾ SM NA. VDP NA when using Merrill altimeter setting.	MISSED APPROACH: Climb to 4000 direct HAXAN and hold.
-----------	---	--

AWOS-3 119.025	MINNEAPOLIS CENTER 124.4 317.7	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



4 NM Holding Pattern HORMA				VGSi and descent angles not coincident (VGSi Angle 3.00/TCH 37).		4000	HAXAN
4000 ← 336°				156° →	156°	ICESA	FIMEK 2.2 NM to RWY 16
				3000	3.00° TCH 45	2200	1.7 NM to RWY 16
				7 NM	2.5 NM	0.5	1.7
CATEGORY	A	B	C	D			
LP MDA	2040-1	581 (600-1)	2040-1¾	581 (600-1¾)			
LNAV MDA	2060-1	601 (600-1)	2060-1¾	601 (600-1¾)			
CIRCLING	2060-1	582 (600-1)	2060-1¾ 582 (600-1¾)	2180-2¼ 702 (800-2¼)			

EC-3, 04 SEP 2025 to 02 OCT 2025

EC-3, 04 SEP 2025 to 02 OCT 2025