

WAAS

CH **62812**

W17A

APP CRS

170°

Rwy Idg

4400

TDZE

769

Apt Elev

769

RNAV (GPS) RWY 17

HANNIBAL RGNL (H.A.E.)

▼

▲ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Quincy altimeter setting; increase all DA 41 feet, all MDA 60 feet, increase LNAV Cat C visibility ¼ SM and Circling Cat C visibility ¼ SM. Baro-VNAV and VDP NA when using Quincy altimeter setting.

MISSED APPROACH: Climb to 3000 direct PARCK and hold.

AWOS-3PT 120.775	KANSAS CITY CENTER 126.225 317.775	UNICOM 122.8(CTAF) 0
----------------------------	--	--------------------------------

ELEV 769

TDZE 769

170°

4

4000 x 100

35

4 NM Holding Pattern

DORUW

3000

←350°

→170°

GP 3.00°

TCH 40

LAMOO

OBEDE 2.5 NM to RW17

*1600

*1 NM to RW17

RW17

*LNAV only

CATEGORY	A	B	C	D
LPV DA	1019-1	250 (300-1)		NA
LNAV/VNAV DA	1079-1¼	310 (400-1¼)		NA
LNAV MDA	1120-1	351 (400-1)		NA
CIRCLING	1260-1	491 (500-1)	1640-2½ 871 (900-2½)	NA

MIRL Rwy 17-35 0

REIL Rwy 17 and 35 0

HANNIBAL, MISSOURI

Orig-A 25MAR21

39°44'N-91°27' W

HANNIBAL RGNL (H.A.E.)

RNAV (GPS) RWY 17