

When local altimeter setting not received, use Vernal altimeter setting and increase all MDA 80 feet, FOSLA fix minimums, increase Cat C visibility ¼ SM.

MISSED APPROACH: Climbing right turn to 9000 direct MTU VOR/DME and hold, continue climb-in-hold to 9000.

AWOS-3P 118.975	SALT LAKE CENTER 135.77 257.7	UNICOM 122.8 (CTAF) 0
--------------------	----------------------------------	--------------------------

One Minute Holding Pattern				9000	MTU
8500 ← 160° / 340° →					
FOSLA MTU 5.2				MARPK MTU 8.2	
6280					
5.2 NM				3 NM	
CATEGORY	A	B	C	D	
CIRCLING	6280-1¼ 1104 (1200-1¼)	6280-1½ 1104 (1200-1½)	6280-3 1104 (1200-3)	6340-3 1164 (1200-3)	
FOSLA FIX MINIMUMS					
CIRCLING	5760-1 584 (600-1)	5900-1 724 (800-1)	6020-2½ 844 (900-2½)	6340-3 1164 (1200-3)	
					FAF to MAP 8.2 NM
					MIRL Rwy 7-25 0 REIL Rwy 7 and 25 0
					Knots 60 90 120 150 180 Min:Sec 8:12 5:28 4:06 3:17 2:44

ROOSEVELT, UTAH

Amtd 4 10NOV16

40°17'N-110°03'W

ROOSEVELT MUNI (74V)

VOR-A