

WAAS CH 53316 W35A	APP CRS 351°	Rwy Idg TDZE 5 Apt Elev 5
--	------------------------	---



RNAV (GPS) RWY 35
MARCO ISLAND EXEC (MKY)

RNP APCH-GPS.

▼ Baro-VNAV and VDP NA when using APF altimeter setting. Rwy 35 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C or above 54°C. When local altimeter setting not received, use APF altimeter setting and increase LPV DA to 312 feet; increase LNAV/VNAV DA to 420 feet; increase all MDAs 40 feet and Circling visibility Cat C $\frac{1}{4}$ SM.

⚠ MISSED APPROACH: Climb to 3000 direct AVCOF and hold, continue climb-in-hold to 3000.

AWOS-3PT 120.075	FORT MYERS APP CON ★ 124.125 371.85	CLNC DEL 120.8	UNICOM 122.7 (CTAF) 0
----------------------------	---	--------------------------	---------------------------------



3000	AVCOF	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 32).			
4 NM	ONS AW	Holding Pattern			
1.5 NM to RW35	PARYE	1500	351°	171°	6000 2000
1.5 NM	3 NM	6.1 NM	GP 3.00° TCH 40		
CATEGORY	A	B	C	D	
LPV DA	286-1 281 (300-1)				
LNAV/VNAV DA	394-1½ 389 (400-1½)				
LNAV MDA	520-1	515 (600-1)	520-1½ 515 (600-1½)	520-1¾ 515 (600-1¾)	
CIRCLING	620-1	615 (700-1)	660-1¾ 655 (700-1¾)	840-2¾ 835 (900-2¾)	

SE-3, 04 SEP 2025 to 02 OCT 2025

SE-3, 04 SEP 2025 to 02 OCT 2025