

▼

NA


W

Baro-VNAV NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 42°C (107°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.
Use Moultrie altimeter setting, when not received, use Tallahassee Intl altimeter setting and increase LPV DA to 609, LNAV/VNAV DA to 653, and all MDA 60 feet; increase LPV and LNAV/VNAV all Cats and LNAV Cats C/D visibility 1/8 SM and increase Circling Cats C/D visibility 1/4 SM.

MISSED APPROACH:
Climb to 3000 direct YALUC and hold.


TALLAHASSEE APP CON★
128.7 254.3

UNICOM
122.7 (CTAF)



ELEV **264**

TDZE **261**



3000

↑

YALUC

✦

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 27).

ILAYI

2000

305°

3000

GP 3.00°

TCH 55

5.4 NM

6.8 NM

CATEGORY	A		B	C	D
LPV DA	565-1 304 (300-1)				
LNAV/VNAV DA	609-1½ 348 (400-1½)				
LNAV MDA	900-1 639 (700-1)		900-1½ 639 (700-1½)		
CIRCLING	900-1 636 (700-1)		1020-2¼ 756 (800-2¼)		1020-2½ 756 (800-2½)