



WAAS CH 40029 W31A	APP CRS 311°	Rwy Idg 7000 TDZE 202 Apt Elev 208
--	------------------------	---

RNAV (GPS) RWY 31

GRENADA MUNI (GNTF)

RNP APCH.	Baro-VNAV and VDP NA when using Greenwood altimeter setting. Rwy 31 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -9°C or above 46°C. When local altimeter setting not received use Greenwood altimeter setting: increase all DAs 65 feet and visibility LNAV/VNAV Cat C and D $\frac{1}{8}$ SM; increase all MDAs 80 feet and visibility LNAV Cats C and D and Circling all Cats $\frac{5}{8}$ SM. Circling Rwy 4, 22, NA at night.	MISSED APPROACH: Climb to 3000 direct WUKNA and hold.
-----------	---	--

AWOS-3PT 118.025	MEMPHIS CENTER 128.5 279.55	UNICOM 122.8 (CTAF)
----------------------------	---------------------------------------	-------------------------------



ELEV 208	TDZE 202	RNAV (GPS) RWY 31			
MIRL Rwy 13-31		GP 3.10° TCH 59			
CATEGORY		A	B	C	D
LPV DA		513-1 311 (400-1)			
LNAV/VNAV DA		679-1½ 477 (500-1½)			
LNAV MDA		720-1 518 (600-1)	720-1¼ 518 (600-1¼)		
CIRCLING		1000-1 792 (800-1)	1000-2¼ 792 (800-2¼)	1060-2¾ 852 (900-2¾)	

SC-4, 04 SEP 2025 to 02 OCT 2025

SC-4, 04 SEP 2025 to 02 OCT 2025