

LOC/DME I-EVW	APP CRS	Rwy Idg	7300
108.9	234°	TDZE	7143
Chan 26		Apt Elev	7143

ILS or LOC/DME RWY 23

EVANSTON-UINTA COUNTY BURNS FLD (E V W)


⚠

For inoperative MALSR, increase S-LOC 23 Cat D visibility to 1 mile. When local altimeter setting not received, procedure NA.

MALSR

MISSED APPROACH: Climb to 7600 then climbing left turn to 12000 via EVW VOR/DME R-213 to COOL/ EVW VOR/DME 16.6 DME and hold, continue climb-in-hold to 12000.

ASOS	SALT LAKE CENTER	GCO	UNICOM
120.0	127.7 354.125	121.72	123.0 (CTAF) 0



ELEV 7143

TDZE 7143

7600	12000	COOL	Use I-EVW DME when on the localizer course.
↑	EVW R-213	△	*LOC only

I-EVW 1.4

JADUR I-EVW 3.1

CESLA I-EVW 7.3

EMUME I-EVW 16

9100

9100

9900

7700*

7300

7200

054°

234°

234°

054°

GS 3.00°

TCH 47

0.8

0.9 NM

4.2 NM

8.7 NM

CATEGORY	A	B	C	D
S-ILS 23	7343-½ 200 (200-½)			
S-LOC 23	7440-½ 297 (300-½)			7440-¾ 297 (300-¾)
CIRCLING	7680-1 537 (600-1)	7760-1 617 (700-1)	7800-1¾ 657 (700-1¾)	8000-2¾ 857 (900-2¾)

REIL Rwy 5 0

HIRL Rwy 5-23 0