

WAAS
CH **99610**
W33A

APP CRS
326°

Rwy Idg
TDZE **10**
Apt Elev **10**

5001

RNAV (GPS) RWY 33


SOUTHLAND FLD (UXL)

RNP APCH-GPS.

Baro-VNAV NA when using Lake Charles Rgnl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C or above 49°C. Rwy 33 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Lake Charles Rgnl altimeter setting and increase LPV DA to 367 feet; increase LNAV/VNAV DA to 403 feet and all visibilities ½ SM; increase all MDAs 20 feet and Circling visibility Cat C/D ¼ SM.

MISSED APPROACH: Climb to 2500 direct HICHY and via 253° track to OFERS and hold.

AWOS-3PT 118.175	LAKE CHARLES APP CON ★ 119.35 282.3	UNICOM 122.8 (CTAF) 0
----------------------------	---	---------------------------------



ELEV 10

TDZE 10

2500

HICHY

tr 253°

OFERS

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).

*LNAV only

HUKIL 2 NM to RW33

RW33

WERUM

OGOG

Procedure Turn NA

326°

1700

GP 3.00°

TCH 40

2 NM

3.1 NM

6 NM

CATEGORY	A	B	C	D
LPV DA		348-1¼	338 (400-1¼)	
LNAV/VNAV DA		384-1¼	374 (400-1¼)	
LNAV MDA		380-1	370 (400-1)	380-1¼ 370 (400-1¼)
CIRCLING	420-1 410 (500-1)	520-1 510 (600-1)	680-1¾ 670 (700-1¾)	680-2 670 (700-2)

REIL Rwy 33 0

MIRL Rwy 15-33 0