

WAAS
CH **73031**
W17A

APP CRS
166°

Rwy Idg
TDZE
Apt Elev

6102
4297
4322

RNAV (GPS) RWY 17
BOULINDER FLD/TOOELE VALLEY (TVY)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -23°C (-9°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM, increase LNAV Cat C/D visibility to 1 SM.

MALSR

MISSED APPROACH:

Climb to 4800 then climbing right turn to 8600 direct WEGET and track 346° to FOGEM and hold.

AWOS-3 119.725	SALT LAKE CITY APP CON 135.5 316.15	CLNC DEL 124.4	UNICOM 123.0 (CTAF)
--------------------------	---	--------------------------	-------------------------------

Procedure NA for arrival at EMONT on V257 northbound, and V236 northeast bound.

Key features and data points:

- WEGET (6100):** 7 NM Holding Pattern, 166° heading.
- JONEK (4379):** (FAF) JONEK, 4379.
- RWY 17 (4371):** 4371.
- Missed Approach:** Climb to 4800, then climbing right turn to 8600 direct WEGET and track 346° to FOGEM and hold.
- Altitudes:** 6100 (6.8), 9800 (7.6), 4379, 4371, 4591 ±.
- Distances:** 7 NM, 6.8 NM, 4.6 NM, 1 NM.
- Angles:** 166°, 346°, 333°.
- Obstacles:** 6649, 6596, 5000, 9141, 9345, 9486, 5543.
- MSA RW17 25 NM:** 12600.

7 NM Holding Pattern

WEGET

8100

346°

166°

GP 3.00° TCH 55

4800

8600

WEGET

tr 346°

FOGEM

* LNAV only

6100

6100

* 1 NM to RWY 17

RWY 17

6.8 NM

4.6 NM

1 NM

CATEGORY	A	B	C	D
LPV DA	4497-½	200 (200-½)		
LNAV/VNAV DA	4547-½	250 (300-½)		
LNAV MDA	4640-½	343 (400-½)	4640-⅝	343 (400-⅝)
CIRCLING	4820-1 498 (500-1)	4900-1 578 (600-1)	5060-2 738 (800-2)	5380-3 1058 (1100-3)

ELEV 4322

TDZE 4297

166°

0.85 X 100

6102 X 100

35

REIL Rwy 35

MIRL Rwy 17-35

TOOELE, UTAH

Amtd 4 14SEP17

40°37'N-112°21'W

BOULINDER FLD/TOOELE VALLEY (TVY)

RNAV (GPS) RWY 17