

WAAS CH 61308 W18A	APP CRS 179°	Rwy ldg 6500 TDZE 0 Apt Elev 0
--	------------------------	---



RNAV (GPS) RWY 18
SOUTH LAFOURCHE LEONARD MILLER JR (G.A.O)

RNP APCH - GPS.

⚠ Rwy 18 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting: increase LPV DA to 396 feet and all visibilities $\frac{1}{4}$ SM; increase LNAV/VNAV DA to 361 feet, visibility Cats A and B $\frac{1}{4}$ SM and Cats C and D $\frac{1}{2}$ SM; increase all MDAs 80 feet and LNAV visibility Cats C and D $\frac{3}{4}$ SM and Circling visibility Cats C and D $\frac{1}{4}$ SM. Baro-VNAV and VDP NA when using Louis Armstrong New Orleans Intl altimeter setting.

MISSED APPROACH:
Climb to 520 then climbing right turn to 2000 direct HIKEN and hold.

AWOS-3PT 118.175	NEW ORLEANS APP CON 120.85 256.9	CINC DEL 120.85	UNICOM 123.0 (CTAF) 0
----------------------------	--	---------------------------	---------------------------------



520	2000	HIKEN	4 NM Holding Pattern			
AVER 1.6 NM to RW18		JADUL 1700	HIKEN		359° → 6000 ← 179° 2000	
RW18 1.1 NM to RW18		560	1700		GP 3.00° TCH 51	
1.1		0.5	3.6 NM		6 NM	
CATEGORY	A		B	C	D	
LPV DA	319-1		319 (400-1)			
LNAV/VNAV DA	284-7/8		284 (300-7/8)		284-1	284 (300-1)
LNAV MDA	380-1		380 (400-1)		380-1 3/4 380 (400-1 3/4)	380-2 380 (400-2)
CIRCLING	440-1		560-1		640-1 3/4	
	440 (500-1)		560 (600-1)		640 (700-1 3/4)	