



WAAS CH 81805 W33A	APP CRS 329°	Rwy Ldg TDZE Apt Elev	6000 195 219
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 33

STAFFORD RGNL (RMN)

RNP APCH - GPS.	MALS	MISSED APPROACH: Climb to 700 then climbing left turn to 3000 direct FALKO and hold, continue climb-in-hold to 3000.
Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Circling Rwy 15 NA at night.		

AWOS-3 126.325	QUANTICO APP CON ★ 127.05 290.375	GCO 135.075	UNICOM 122.725 (CTAF) 0
--------------------------	---	-----------------------	--



	700	3000	FALKO	
			△	
			JAVIK 2.4 NM to RW33	
			CODAC 2000	
			RW33	
			1.4 NM	
			1 NM	
			3.2 NM	
			6.2 NM	
			RISVE 3000	
			329°	
			2000	
			GP 3.00° TCH 46	
CATEGORY	A	B	C	D
LPV DA	445-¾	250 (300-¾)		
LNAV/VNAV DA	680-1⅛	485 (500-1⅛)		
LNAV MDA	680-¾	485 (500-¾)	680-1⅛	485 (500-1⅛)
CIRCLING	720-1 501 (600-1)	820-1 601 (700-1)	820-1¾ 601 (700-1¾)	1040-2¾ 821 (900-2¾)