


RNAV (GPS) RWY 19

Procedure NA at night. Rwy 19 helicopter visibility reduction below 1 SM NA.
Obtain local altimeter setting on CTAF; when not received, use Tuscaloosa altimeter setting: increase all MDAs 80 feet; increase LP and LNAV Cat C/D visibility ½ SM; increase Circling visibility all Cats ½ SM.

MISSED APPROACH: Climb to 3000 direct BLANG and hold.

CTAF
122.9 L


$\leftarrow 188^\circ$

Diagram of a beam with a pin support at the bottom and a roller support at the top. A horizontal force of 51.44 kN is applied to the beam. The beam length is 6 m.

3000	BLANG
	

Visual Segment - Obstacles.

4 NM
Holding Pattern



CATEGORY	A	B	C	D
LP MDA	700-1	463 (500-1)	700-1 $\frac{3}{8}$	463 (500-1 $\frac{3}{8}$)
LNAV MDA	800-1	563 (600-1)	800-1 $\frac{5}{8}$	563 (600-1 $\frac{5}{8}$)
CIRCLING	1000-1	763 (800-1)	1000-2 $\frac{1}{4}$ 763 (800-2 $\frac{1}{4}$)	1040-2 $\frac{1}{2}$ 803 (900-2 $\frac{1}{2}$)

NORTH PICKENS (3M8)
RNAV (GPS) RWY 19

SE-4, 04 SEP 2025 to 02 OCT 2025