

APP CRS
031°

Rwy Idg
TDZE
Apt Elev

4000
648
658

RNAV (GPS) RWY 3

RUBY (RBY) (PARY)

When local altimeter setting not received, use Galena altimeter setting and increase all MDA 340 feet and all visibilities ¾ SM. DME/DME RNP-0.3 NA.
Rwy 3 Straight-in and Circling minimums NA at night. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH:
Climbing right turn to 3800 direct WINUR and hold.

AWOS-3P 118.25	ANCHORAGE CENTER 127.0 290.2	FAIRBANKS RADIO 122.25	CTAF 122.8
-------------------	---------------------------------	---------------------------	---------------

Chart details: WINUR (3800) to TINUC (2700) 030°/030°; TINUC (2700) to YARUN (2900) 031°/031°; YARUN (2900) to SOLCO (3800) 031°/031°; SOLCO (3800) to DUCCEL (3800) 031°/031°; DUCCEL (3800) to ZUMUN (3800) 031°/031°; ZUMUN (3800) to WINUR (3800) 031°/031°.

5 NM Holding Pattern

Visual Segment - Obstacles

3800 WINUR

5 NM

210°

030°

030°

031°

2700

1800

6.2 NM

3.2 NM

2.9 NM

0.1

CATEGORY	A	B	C	D
LNVA MDA	1260-1	612 (700-1)	1260-1¾ 612 (700-1¾)	NA
CIRCLING	1260-1 602 (700-1)	1400-1 742 (800-1)	1400-2¼ 742 (800-2¼)	NA

REIL Rwy 21

MIRL Rwy 3-21

RUBY, ALASKA

Amtd 1C 02DEC21

64°44'N-155°28'W

RUBY (RBY) (PARY)

RNAV (GPS) RWY 3