YODUH TWO DEPARTURE (RNAV)

SAN ANTONIO DEP CON 125.1 307.0

RNAV 1 - DME/DME IRU or GPS.

RADAR required for non-GPS equipped aircraft. RADAR required.

TOP ALTITUDE: ASSIGNED BY ATC


NOTE: Aircraft destined for airports north/northeast of DFW terminal area must file the KLNGR Transition.


KLNGR

TAKEOFF MINIMUMS

Rwy 17: Standard with minimum climb of 210'/NM to 2200.

Rwy 35: Standard with minimum climb of 250'/NM to 3800.





04 SEP 2025 to 02 OCT 2025

SC-3,

NOTE: Chart not to scale.

V

DEPARTURE ROUTE DESCRIPTION

<u>TAKEOFF RUNWAY 17:</u> Climb on heading 169° or as assigned by ATC, for vectors to SITHH, thence. . . <u>TAKEOFF RUNWAY 35:</u> Climb on heading 349° or as assigned by ATC, for vectors to SITHH, thence. . .

. . . on track 002° to YODUH, then on transition. Maintain ATC assigned altitude. Expect filed altitude 10 minutes after departure.

KLNGR TRANSITION (YODUH2.KLNGR)
PRTZY TRANSITION (YODUH2.PRTZY)