

WAAS  
CH **62840**  
**W17A**

APP CRS  
**171°**

Rwy Idg  
TDZE **693**  
Apt Elev **693**

**RNAV (GPS) RWY 17**

KENNETH COPELAND (4T2)

RNP APCH.

NA

Baro-VNAV and VDP NA when using Fort Worth Meacham Intl altimeter setting. Rwy 17 helicopter visibility reduction below 3/4 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Obtain local altimeter setting on CTAF; when not received, use Fort Worth Meacham Intl altimeter setting: Increase LPV DA to 973 feet; increase LNAV/VNAV DA to 1135 feet; increase all MDA 40 feet and LNAV Cat C/D and Circling Cat C visibility 1/4 SM.

MISSED APPROACH: Climb to 1200 then climbing right turn to 3100 direct ODGOY and hold.

LONE STAR APP CON  
**125.8 257.95**

UNICOM  
**123.075 (CTAF) 0**

ODGOY

3000

GP 3.00°  
TCH 40

ZEBAV

2400

CAPUV

2.7 NM to RW17

RW17

5943 x 127

1200

3100

ODGOY

\*1.5 NM to RW17

\*1.580

\*LNAV only.

7 NM

2.6 NM

1.2 NM

1.5 NM

| CATEGORY     | A                        | B                        | C                        | D |
|--------------|--------------------------|--------------------------|--------------------------|---|
| LPV DA       | 943-1 250 (300-1)        |                          |                          |   |
| LNAV/VNAV DA | 1105-13/8 412 (500-13/8) |                          |                          |   |
| LNAV MDA     | 1200-1 507 (600-1)       | 1200-13/8 507 (600-13/8) |                          |   |
| CIRCLING     | 1240-1 547 (600-1)       | 1340-13/4 647 (700-13/4) | 1440-21/2 747 (800-21/2) |   |

LIRL Rwy 17-35 0

FORT WORTH, TEXAS

Orig-A 21MAY20

32°59'N-97°30'W

**RNAV (GPS) RWY 17**

KENNETH COPELAND (4T2)

SC-2, 04 SEP 2025 to 02 OCT 2025