

RNAV (GPS) Y RWY 22

KANE OHE BAY MCAS (PHNG)

T *Circling not authorized SE of Rwy 4-22, CAT D remain within 2.8 NM.

MISSED APPROACH: Climbing right turn to 4200 direct ORIUN and hold.

ASR/
PAR

Knots	60	120	180	240	300	360
V/V(fpm)	290	580	870	1160	1450	1740
Min climb of 290 ft/NM to 2200 - Controlling Obstacle 1838						

NOT FOR CIVIL USE

A-311

CAUTION: Mountainous terrain
E, S, and W of airfield.

1995

EMERG SAFE ALTITUDE 100 NM 12,200

Diagram illustrating the 6 NM Holding Pattern for ORION (TA 18,000). The pattern is a right-hand circle with a 6 NM radius. The holding pattern is centered on the 033° heading. The pattern includes a 1 NM segment, a 3.8 NM segment, and a 1 NM segment. The holding pattern is defined by a 6 NM radius. The holding pattern is defined by a 6 NM radius. The holding pattern is defined by a 6 NM radius.

CATEGORY	A	B	C	D
INAV MDA	NOT AUTHORIZED			660-134 637 (700-134)
 CIRCLING*	NOT AUTHORIZED			960-3 937 (1000-3)

RNAV (GPS) Y RWY 22