

LOC I-BLV 109.9	APP CRS 319°	Rwy Ldg TDZE Apt Elev
		7822 439 459

ILS or LOC RWY 32L

SCOTT AFB/MIDAMERICA ST LOUIS (BLV)

DME required.

⚠



For inop ALS, increase S-ILS 32L Cat E visibility to RVR 4000 and increase S-LOC 32L Cat C/D/E visibility to 1½ SM. Procedure turn NA for Cat E aircraft. DME from SKE TACAN. Simultaneous reception of I-BLV and SKE DME required. *RVR 1800 authorized with use of FD or AP or HUD to DA.

ALSF-1

MISSED APPROACH:

Climb to 1500 then climbing left turn to 2400 direct SKE TACAN and on SKE R-139 to TIBLY INT/ SKE 14.1 DME and hold.

ATIS 128.7 256.7	ST LOUIS APP CON 125.2 281.5	SCOTT TOWER 128.25 253.5	GND CON 199.2 275.8
----------------------------	--	------------------------------------	-------------------------------



1500	2400	SKE	SKE R-139	TIBLY INT	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 50). Remain within 10 NM
CATEGORY A B C D E					
S-ILS 32L * 639/24 200 (200-½)					
S-LOC 32L 920/24 481 (500-½) 920/50 481 (500-1)					
CIRCLING 1000-1 541 (600-1) 1120-1 661 (700-1) 1240-2¼ 781 (800-2¼) 1240-2½ 781 (800-2½) 1240-2¾ 781 (800-2¾)					