

CLEVELAND, OHIO

AL-84 (FAA)


25275

WAAS CH 56204 W06A	APP CRS 058°	Rwy Ldg 9000 TDZE 773 Apt Elev 799
--	------------------------	---


RNAV (GPS) Y RWY 6L
CLEVELAND-HOPKINS INTL (CLE)

RNP APCH. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). Circling Rwy 10 NA at night. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 5500 and increase LNAV Cats C/D visibility to 1½ SM.	ALSF-2 ⓐ	MISSED APPROACH: Climb to 3000 direct ACAPO and on track 001° to PASLE and hold.
---	-------------	--

D-ATIS 127.85	CLEVELAND APP CON 126.55 346.325	CLEVELAND TOWER 124.5 273.45	GND CON 121.7 273.45
-------------------------	--	--	--------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).		3000	ACAPO	PASLE
BETLL				tr 001°
2900		DEVYL	BOEER	*LNAV only.
2300		2000	*1.3 NM to RWY 06L	RWY 06L
2000				
GP 3.00° TCH 55		1.9 NM	1.1 NM	2.4 NM
CATEGORY	A	B	C	D
LPV DA	973/18		200 (200-½)	
LNAV/VNAV DA	1120/30		347 (400-⅝)	
LNAV MDA	1260/24	487 (500-½)	1260/50	487 (500-1)
CIRCLING	1420-1	621 (700-1)	1420-1¾ 621 (700-1¾)	1420-2 621 (700-2)



CLEVELAND, OHIO
Amdt 2A 21JUN18

41°25'N-81°51'W

CLEVELAND-HOPKINS INTL (CLE)
RNAV (GPS) Y RWY 6L

EC-2, 02 OCT 2025 to 30 OCT 2025

EC-2, 02 OCT 2025 to 30 OCT 2025