

WAAS CH 72808 W31A	APP CRS 313°	Rwy Idg TDZE 477 Apt Elev 487
--	------------------------	---

RNAV (GPS) Y RWY 31L

DALLAS LOVE FLD (DAL)

RNP APCH.

Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations. For inop ALS, increase LPV all Cats visibility to RVR 4500.

MALSR

MISSED APPROACH: Climb to 1700 then climbing right turn to 4000 direct TADDI and hold.

D-ATIS 120.15	LONE STAR APP CON NORTH 124.3 282.275 SOUTH 125.2 343.65	LOVE TOWER 123.7 239.3	GND CON 121.75 348.6	CLNC DEL 127.9	CPDLC
-------------------------	--	----------------------------------	--------------------------------	--------------------------	-------

ELEV 487 **D** TDZE 477

TDZ/CL Rwy 13L and 31L	HIRL Rwy 13L-31R, and 13R-31L
------------------------	-------------------------------

1700 4000 TADDI

*LNAV only.

RW31L

GIYET 3.3 NM to RW31L

JAKID 2200

MYLES 2500

ORVLL 3000 276° (12.1)

YEAGR 3000 276° (12.1)

2.5 NM

0.8 NM

1.8 NM

9.9 NM

CATEGORY	A	B	C	D
LPV DA	770/22	293 (300-½)		
LNAV MDA	1360/40	883 (900-¾)	1360-2	883 (900-2)
C CIRCLING	1360-1¼	873 (900-1¼)	1360-2½ 873 (900-2½)	1520-3 1033 (1100-3)

GP 3.08°

TCH 55

DALLAS, TEXAS

32°51'N-96°51'W

DALLAS LOVE FLD (DAL)

RNAV (GPS) Y RWY 31L

Amdt 1E 13SEP18