


ATIS 370.925 ★		RADAR required		[USN]					
GND CON				Rwy	Knots	60	120	180	240
251.15				7	⊕	V/V(fpm)	276	552	828
NAVY FALLON TOWER ★				13L/R	⊕	V/V(fpm)	211	422	633
119.25 340.2									
NAVY FALLON DEP CON ★									
120.85 360.2									


TOP ALTITUDE:
ASSIGNED BY ATC

Minimum Climb Rate
⊕ to 5200
⊕ to 5400

CAUTION: Fallon Muni Airport
(uncontrolled) 5 NM NW pattern
alt 800' AGL.



FALLON
Chan 82 NFL



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 7: Climb heading 074° to 4500, then climbing left turn heading 283°, maintain 5900 or ATC assigned altitude, thence...

TAKEOFF RWY 13 L/R: Climb on heading 131° to 4500, then climbing right turn heading 340°, maintain 5900 or ATC assigned altitude, thence...

TAKEOFF RWY 25: Climb on heading 254° to 4500, then climbing right turn heading 005°, maintain 5900 or ATC assigned altitude, thence...

TAKEOFF RWY 31 L/R: Climb on heading 321°, maintain 5900 or ATC assigned altitude, thence...

...expect radar vectors to first enroute navaid/fix. Expect clearance to requested altitude/flight level five minutes after departure.