


WAAS CH 72624 W05A	APP CRS 051°	Rwy Ldg 5545 TDZE 15 Apt Elev 17
--	------------------------	---

RNAV (GPS) RWY 5

PAGE FLD (FMY)

RNP APCH.	When Circling to Rwy 31 at night, operational VGSI required, remain on or above VGSI glidepath until threshold. Rwy 5 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 4°C or above 54°C.	MISSED APPROACH: Climb to 2600 direct IBITE and on track 002° to SERFS and hold.
-----------	--	--

ATIS 123.725	FORT MYERS APP CON ★ 125.15 306.2 (Rwys 5, 13) 126.8 306.2 (Rwys 23, 31)	PAGE TOWER ★ 119.0 (CTAF) 306.95	GND CON 121.7	CLNC DEL 121.7
------------------------	--	---	-------------------------	--------------------------



ELEV 17		D TDZE 15	
IBITE		SERFS	
2600		tr 002°	
UZAWO		GRAMS	
2000		2000	
GP 3.00°		HADMO 2 NM to RW05	
TCH 53		*1.1 NM to RW05	
6.8 NM		0.9 NM	
A		B	
LPV DA		265-¾ 250 (300-¾)	
LNAV/VNAV DA		317-7/8 302 (300-7/8)	
LNAV MDA		420-1 405 (500-1)	
CIRCLING		540-1 523 (600-1)	
		600-1½ 583 (600-1½)	
		680-2 663 (700-2)	