

RNAV (RNP) Z RWY 27
HELENA RGNL (HLN)

*Missed approach requires minimum climb of 280 feet per NM to 7800.
#Missed approach requires minimum climb of 375 feet per NM to 6300.

Procedure NA for arrivals at HLN VORTAC on V113 northeast bound.

(IAF) RICHD (RNP 0.40) 12000 to HLN 090° (19.7) 271° (11)

(IAF) HELENA HLN (RNP 0.40) RW27 11000 271° (8.2) 124° (6.5)

(IF) AGUPY 210K 10200 126° (3.4) 271° (2)

(FAF) JEXUT 7000 (1.3) 271° (2.8)

GOKME 6500 271° (2)

FABGO 7000 (2.1)

EJUPY 8200 (1.7)

DEPTH 8700 (2.4)

CAGIN 8700 (2.4)

(IF) BOSCA 210K 7200 225° (6.5)

(IAF) SWEDD (RNP 0.40) 10000 7200 312° (7.9)

(IAF) LUNGE (RNP 0.40) 9400 271° (17.5)

(IAF) HEXOL (RNP 0.40) 9400 258° (15.2)

FALDE 9400 173° (21)

MSA RW 27 25 NM 10600

MISSED APCH FIX

PIXXI 090° 270° 7 NM


KELTY 275° (11.9)

KISTY 265° (9)

(not to scale)

Procedure NA for arrivals at

--	--



12000 ↑ tr 271°	KISTY ✠ tr 265°	KELTY △ tr 275°	PIXXI △	JEXUT 6500	GOKME 7000
See planview for multiple IF locations.					
CATEGORY	A	B	C	D	
RNP 0.13 DA*		4172-½	320 (300-½)		
RNP 0.20 DA#		4303-⅞	451 (500-⅞)		
RNP 0.30 DA#		4353-1	501 (500-1)		
RNP 0.30 DA		4866-4	1014 (1000-4)		

AUTHORIZATION REQUIRED