

LOC/DME I-OIB <u>109.9</u> Chan 36	APP CRS 221°	Rwy Idg 7602 TDZE 41 Apt Elev 46
--	------------------------	---

LOC RWY 22
WILLIAM P HOBBY (HOU)

RNAV 1-GPS required. RADAR required for procedure entry.

T
A For inop ALS, increase S-LOC 22 Cat C/D/E visibility to 1 3/8 SM.

MALS



MISSED APPROACH: Climb to 3000 direct EISEN and on track 225° to ACOLA and hold.

D-ATIS 124.6	HOUSTON APP CON 120.05 379.1 EAST 124.35 316.15 WEST	HOBBY TOWER 118.7 256.9	GND CON 121.9	CLNC DEL 125.45	CPDLC
------------------------	--	-----------------------------------	-------------------------	---------------------------	-------




Diagram illustrating the S-LOC 22 approach for the KAFDO INT I-OB. The diagram shows a 3.05° glide path (TCH 49) starting from a 1.3 NM distance from the I-OB (1.1 NM) and ending at the 2000 ft I-OB (12 NM). The approach is divided into five categories: A (500-3/4 459 (500-3/4)), B (520-1 474 (500-1)), C (540-1 1/2 494 (500-1 1/2)), D (740-2 1/4 694 (700-2 1/4)), and E (820-2 3/4 774 (800-2 3/4)). The diagram also shows the 3000 ft EISEN and ACOLA I-OBs, and the 225° heading.

CATEGORY	A	B	C	D	E
S-LOC 22	500-3/4 459 (500-3/4)	520-1 474 (500-1)	500-1 459 (500-1)		
C CIRCLING	500-1 454 (500-1)	520-1 474 (500-1)	540-1 1/2 494 (500-1 1/2)	740-2 1/4 694 (700-2 1/4)	820-2 3/4 774 (800-2 3/4)

