

APP CRS 320°	Rwy Ldg	7278
	TDZE	793
	Apt Elev	796

RNAV (RNP) Z RWY 32

INDIANAPOLIS INTL (IND)

▼

For uncompensated Baro-VNAV systems, procedure NA below -18°C (2°F) or above 54°C (130°F). GPS required.

MALSR

MISSED APPROACH: Climb to 3000 on track 320° to KEADY and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC
------------------	---------------------------------------	---------------------------	------------------	--------------------------	-------

The main chart displays the RNP Z RWY 32 procedure. Key features include:

- Initial Approach:** (IF) CRCL 6000 210K (RF REQD) at 4400 ft, 140°/5.3.
- Intermediate Approach:** (IF) HNKLE 5000 210K (RF REQD) at 3600 ft, 205°/4.2.
- Final Approach:** (FAF) BTTLR at 2400 ft, 320°/4.9.
- Obstacles:** HIKEK (3600 ft, 075°/4.2), BDAWG (5000 ft, RF REQD), EVAVE (200K), CUREG (200K), DLNGR (3600 ft, 12°/9).
- Missed Approach:** MISSED APCH FIX at 4 NM, 139°/3.19° to KEADY.
- MSA:** MSA RW32 25 NM, 3100 ft.
- Altitudes:** ELEV 796, TDZE 793.

ELEV 796

D

TDZE 793

3000 KEADY

Ir 320°

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

BTTLR 2400

GP 3.00° TCH 53

RW32

See planview for multiple IF locations.

4.9 NM

CATEGORY	A	B	C	D
RNP 0.19 DA		1134/30	341 (400-%)	
RNP 0.30 DA		1196/45	403 (400-%)	

AUTHORIZATION REQUIRED

INDIANAPOLIS, INDIANA

Amdt 2 10NOV16

39°43'N-86°18'W

INDIANAPOLIS INTL (IND)

RNAV (RNP) Z RWY 32