

WAAS CH 77706 W23B	APP CRS 230°	Rwy Ldg 11200 TDZE 783 Apt Elev 796
--	------------------------	--

RNAV (GPS) Y RWY 23R
INDIANAPOLIS INTL (IND)

▼ or above 54°C [130°F]. DME/DME RNP-0.3 NA. For inoperative ALS, increase LNAV Cat C/D visibility to RVR 6000. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

▲ **RVR 1800 authorized with use of FD or AP or HUD to DA.


MALSR




MISSED APPROACH:
Climb to 1500 then
climbing right turn to
3000 direct KEADY
and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC
------------------	---------------------------------------	---------------------------	------------------	--------------------------	-------

Procedure NA for arrivals at CLANG
on V14-192-210 northeast bound.



ELEV 796	D	TDZE 783
----------	----------	----------



VGS and RNAV glidepath not coincident (VGS Angle 3.00/TCH 71).

CATEGORY	A	B	C	D
LPV DA	**983/24 200 (200-½)			
LNAV/VNAV DA	1165/40 382 (400-¾)			
LNAV MDA	1200/24 417 (500-½)	1200/40 417 (500-¾)		
CIRCLING	1420-1 624 (700-1)	1420-1¾ 624 (700-1¾)	1560-2½ 764 (800-2½)	