

WAAS CH 58126 W24A	APP CRS 244°	Rwy Idg TDZE Apt Elev	3856 545 546
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 24

BOWMAN FLD (LOU)

RNP APCH - GPS.

VDP NA with Louisville Muhammad Ali Intl altimeter setting. When local altimeter setting not received, use Louisville Muhammad Ali Intl altimeter setting. Rwy 24 helicopter visibility reduction below ¾ SM NA. Circling Rwy 6, 15, 33 NA at night.

MISSED APPROACH:
Climb to 1100 then climbing left turn to 3000 direct CAANT and hold.

ATIS 124.15	LOUISVILLE APP CON 132.075 327.0	BOWMAN TOWER ★ 119.5 (CTAF) 257.625	GND CON 121.8	CLNC DEL 118.9	UNICOM 122.95
-----------------------	--	---	-------------------------	--------------------------	-------------------------

ELEV 546

D

TDZE 545

1100

3000

CAANT

*RNAV only

RUHEE 2 NM to RW24

*1.1 NM to RW24

RW24

BNNUS 2300

NUNYA 3000

GP 3.00°

TCH 53

1.1 NM

0.9 NM

3.4 NM

5 NM

CATEGORY	A	B	C	D
LPV DA	830-7 ⁵ / ₈	285 (300-7 ⁵ / ₈)	NA	
RNAV/VNAV DA	1025-1 ⁵ / ₈	480 (500-1 ⁵ / ₈)	NA	
RNAV MDA	1000-1	455 (500-1)	NA	
CIRCLING	1060-1 514 (600-1)	1080-1 534 (600-1)	NA	

REIL Rws 24 and 33
MIRL Rws 6-24 and 15-33