



WAAS CH 78128 W18A	APP CRS 183°	Rwy Ldg TDZE 217 Apt Elev 219
--	------------------------	---

RNAV (GPS) RWY 18
MOBILE RGNL (MOB)

RNP APCH - GPS. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 42°C. Rwy 18 helicopter visibility reduction below ¾ SM NA.	MISSED APPROACH: Climb to 2000 direct IPAPE and hold.
--	---

ATIS 124.75 257.85	MOBILE APP CON ★ 118.5 269.3	MOBILE TOWER ★ 118.3 (CTAF) 0 239.0	GND CON 121.9 348.6	UNICOM 122.95
------------------------------	--	---	-------------------------------	-------------------------



4 NM Holding Pattern		CECAP	BAKAY	DIDECE 2.7 NM to RWY 18	1.3 NM to RWY 18
6000 2000		GP 3.00° TCH 45	2000	1120	
		6.8 NM	2.8 NM	1.4 NM	1.3
CATEGORY	A	B	C	D	
LPV DA	508-1 291 (300-1)				
LNAV/VNAV DA	624-1⅓ 407 (500-1⅓)				
LNAV MDA	640-1	423 (500-1)	640-1¼	423 (500-1¼)	
CIRCLING	680-1	461 (500-1)	740-1½ 521 (600-1½)	780-2 561 (600-2)	

SE-4, 02 OCT 2025 to 30 OCT 2025

SE-4, 02 OCT 2025 to 30 OCT 2025