

WAAS CH 56511 W36A	APP CRS 001°	Rwy Ldg 7800 TDZE 26 Apt Elev 26
--	------------------------	---

RNAV (GPS) RWY 36

MOBILE INTL (BFM)

RNP APCH - GPS.



▼

▲

Rwy 36 helicopter visibility reduction below ¾ SM NA.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -2°C or above 54°C.

MISSED APPROACH:
Climb to 2300 direct
WORIR and hold.

ATIS 135.575	MOBILE APP CON ★ 118.5 269.3	INTERNATIONAL TOWER ★ 118.8 (CTAF) 0 251.1	GND CON 121.7 239.3	UNICOM 122.95
------------------------	--	--	-------------------------------	-------------------------



2300

↑

WORIR

△

VGSI and RNAV glidepath not coincident

(VGSI Angle 3.00/TCH 62).

4 NM

Holding Pattern

POCIP

181° → 6000

← 001° 2000

GP 3.00°

TCH 50

OJMEM

3 NM to RW36

KUBEC

1800

1.1 NM to RW36

1800

1020

1.1 NM

1.9 NM

2.5 NM

7 NM

CATEGORY

A

B

C

D

LPV

DA

304-1

278 (300-1)

LNAV/VNAV

DA

364-1

338 (400-1)

LNAV

MDA

440-1

414 (500-1)

440-1½

414 (500-1½)

CIRCLING

680-1

654 (700-1)

680-1¾

654 (700-1¾)

1100-3

1074 (1100-3)