

VORTAC BFM 116.35 Chan 110(Y)	APP CRS 333°	Rwy Ldg TDZE 25 Apt Elev 26
---	------------------------	---


VOR RWY 32
MOBILE INTL (BFM)

⚠ When local altimeter setting not received, use Mobile Rgnl altimeter setting and increase all MDAs 60 feet. For inop MALSR, increase S-32 Cats C/D visibility to 1¾ SM. For inop MALSR when using Mobile Rgnl altimeter setting, increase S-32 Cats C/D visibility to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 600 then climbing right turn to 2000 via heading 040° and BFM VORTAC R-031 to STETS INT and hold.

ATIS 135.575	MOBILE APP CON ★ 118.5 269.3	INTERNATIONAL TOWER★ 118.8(CTAF) 0 251.1	GND CON 121.7 239.3	UNICOM 122.95
------------------------	--	--	-------------------------------	-------------------------



ELEV 26	TDZE 25
81	7800 X 150
TWR	36
32	333°

REIL Rwy 14
MIRL Rwy 18-36
HIRL Rwy 14-32
TDZ/CL Rwy 32

600	2000	BFM R-031	STETS
↑	hdg 040°	△	

BFM VORTAC

153°

1800

333°

0.1 1.3

CATEGORY	A	B	C	D
S-32	540/24	515 (600-½)	540/55	515 (600-1)
CIRCLING	680-1	654 (700-1)	680-1¾ 654 (700-1¾)	1100-3 1074 (1000-3)

SE-4, 02 OCT 2025 to 30 OCT 2025

SE-4, 02 OCT 2025 to 30 OCT 2025