

25275

RNAV (GPS) RWY 32

MUSKEGON COUNTY (MKG)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18° C or above 54°C.
▲ For inop ALS, increase LPV visibility all Cats to RVR 4000, LNAV/VNAV visibility all Cats to RVR 4500, and LNAV visibility Cats A/B to RVR 5500 and Cats C/D to 1½ SM.
 ** RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using Fremont altimeter setting.

MISSED APPROACH:
Climb to 2300 direct
NENUE and hold.

*** INAV only**

RWY 32
2300

NENUE

PADBE
2200

SINNI
2700

4 NM Holding Pattern

1.3 NM to RWY 32

321°

322°

142° → 6000
← 322° 2700

GP 3.00°
TCH 50

CATEGORY	A	B	C	D
LPV DA**	829/24		200 (200-½)	
LNAV/DA VNAV	915/24		286 (300-½)	
LNAV MDA	1080/24	451 (500-½)	1080/45	451 (500-¾)
CIRCLING	1080-1 451 (500-1)	1180-1 551 (600-1)	1200-1½ 571 (600-1½)	1200-2 571 (600-2)

MUSKEGON COUNTY (MKG)
RNAV (GPS) RWY 32

EC-1, 02 OCT 2025 to 30 OCT 2025