

WAAS CH 70613 W02B	APP CRS 021°	Rwy Ldg 7601 TDZE 587 Apt Elev 599
--	------------------------	---

APP CRS
021°

Rwy Ldg	7601
TDZE	587
Apt Elev	599

RNAV (GPS) Y RWY 2C
NASHVILLE INTL (BNA)

RNP APCH - GPS.

T Simultaneous approach authorized. INAV procedure NA during simultaneous operations.
A Use of FD or AP providing RNAV track guidance required during simultaneous operations.
 For uncompensated Baro-VNAV systems, INAV/VNAV NA below -10°C or above 54°C.
 For non APS, increase INAV/VNAV all Cats to RVR 4500 and INAV Cat C and D visibility to RVR 6000. **RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR







MISSED APPROACH:
Climb to 4000 direct
TANDS and hold.

D-ATIS
135.1

NASHVILLE APP CON
118.4 360.7 (030°-196°)
119.35 372.0 (197°-029°)

NASHVILLE TOWER
118.6 257.8

GND CON
121.9 348.6



NASHVILLE, TENNESSEE
Amdt 3 02OCT25

36°07'N-86°41'W

NASHVILLE INTL (BNA)

RNAV (GPS) Y RWY 2C