


WAAS CH 70324 W22A	APP CRS 219°	Rwy Ldg 8205 TDZE 11 Apt Elev 17
--	------------------------	---

RNAV (GPS) Z RWY 22L

NEWARK LIBERTY INTL (EWR)

RNP APCH - GPS.		ALSF-2		MISSED APPROACH: Climb to 3000 direct TAYCU and on track 252° to KILMA and hold.	
CIRCLING NA south of Rwy 11-29. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C. When Circling to Rwy 29 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.					
D-ATIS 115.7 134.825	NEWARK APP CON 128.55 379.9	NEWARK TOWER 118.3 257.6		GND CON 121.8	CLNC DEL 118.85
				CPDLC	



3000	TAYCU	tr 252°	KILMA	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 60°).	
CATEGORY		A	B	C	D
LPV DA		211/18		200 (200-½)	
LNAV/VNAV DA		462/45		451 (500-¾)	
LNAV MDA		560/24	549 (600-½)	560/60	549 (600-1¼)
CIRCLING		660-1	643 (700-1)	900-2¾ 883 (900-2¾)	900-3 883 (900-3)

