

VORTAC HRV <u>114.1</u> Chan 88	APP CRS 351°	Rwy Idg 5135 TDZE 8 Apt Elev 8
---------------------------------------	------------------------	---


VOR/DME RWY 36L
LAKEFRONT (NEW)


T Visibility reduction by helicopters NA.

A When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting and increase all MDA 40 feet and increase S-36L Cat C/D and Circling Cat D visibilities $\frac{1}{4}$ mile.

MISSED APPROACH: Climb to 2000
via HRV R-351 and RQR R-082 to
SNAKI INT/RQR 36.6 DME and hold.

ATIS 124.9	NEW ORLEANS APP CON NORTH 133.15 290.3 SOUTH 123.85 256.9	LAKEFRONT TOWER * 118.95(CTAF) 0	GND CON 121.7 335.575	CLNC DEL 127.4
----------------------	---	--	---------------------------------	--------------------------



2000  HRV R-351	RQR R-082	SNAKI 	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 50).		Procedure Turn NA
* 720 when using Louis Armstrong New Orleans Intl altimeter setting. 					
CATEGORY	A		B	C	D
S-36L	480-1 472 (500-1)			480-1¼ 472 (500-1¼)	480-1½ 472 (500-1½)
CIRCLING	520-1 512 (600-1)			700-2 692 (700-2)	820-2¾ 812 (900-2¾)

