

WAAS CH 73012 W08A	APP CRS 074°	Rwy Idg TDZE 1486 Apt Elev 1497
--	------------------------	---

RNAV (GPS) RWY 8

EASTERN OREGON RGNL AT PENDLETON (PDT)

RNP APCH.

▼
▲


Circling to Rwy 11 NA at night. Baro-VNAV and VDP NA when using Walla Walla altimeter setting. Rwy 8 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Inop table does not apply to LPV all Cats and LNAV Cats C/D. When local altimeter setting not received, use Walla Walla altimeter setting and increase all DA 122 feet and all visibilities ¼ SM. Increase all MDA 140 feet and LNAV Cat C/D and Circling Cat C visibilities ¼ SM and Circling Cat D ½ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM. For inop ALS when using Walla Walla altimeter setting, increase LNAV/VNAV all Cats visibility to 1 ½ SM.

ODALS

MISSED APPROACH:

Climb to 2100 then climbing left turn 5000 to ZUTED and hold.

ASOS 118.325	SPOKANE APP CON * 133.15 379.15	PENDLETON TOWER * 119.7 (CTAF) 257.8	GND CON 121.9 257.8	UNICOM 122.95
------------------------	---	--	-------------------------------	-------------------------



5 NM Holding Pattern

EFAKE

CIMAG

CESMI 2 NM to RW08

*1 NM to RW08

RW08

GP 3.00° TCH 56

6000 4300

254° 074°

074°

3400

6.8 NM 3.8 NM 1 1

2100 5000 ZUTED

*LNAV only

ELEV 1497 D TDZE 1486

REIL Rwy 11 and 29
MIRL Rwy 11-29
HIRL Rwy 8-26

CATEGORY	A	B	C	D
LPV DA		1736-¾ 250 (300-¾)		
LNAV/VNAV DA		1769-¾ 283 (300-¾)		
LNAV MDA	1860-¾ 374 (400-¾)		1860-1 374 (400-1)	
CIRCLING	1920-1 423 (500-1)	1960-1 463 (500-1)	1980-1½ 483 (500-1½)	2200-2¼ 703 (800-2¼)