

WAAS
CH **40004**
W10A

APP CRS
103°

Rwy Idg
TDZE **24**
Apt Elev **31**

RNAV (GPS) Y RWY 10R

PORTLAND INTL (PDX)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized with Rwy 10L. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations.

ALSIF-2

MISSED APPROACH: Climb to 440 then climbing right turn to 5000 direct MULES and hold.

D-ATIS 128.35 269.9	PORTLAND APP CON 124.35 299.2	PORTLAND TOWER Rwy 10L-28R 118.7 257.8 Rwys 3-21, 10R-28L 123.775 251.125	GND CON 121.9 348.6	CLNC DEL 120.125 318.1	CPDLC
---	---	---	-------------------------------	----------------------------------	-------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).				
GP 3.00° TCH 53				
CATEGORY	A	B	C	D
LPV DA	224/18		200 (200-½)	
LNAV/VNAV DA	329/24		305 (300-½)	
LNAV MDA	440/24	416 (500-½)	440/40	416 (500-¾)
CIRCLING	720-1 689 (700-1)	760-1 729 (800-1)	1060-3	1029 (1100-3)

PORTLAND, OREGON
Amdt 2C 08OCT20

45°35'N-122°36'W

PORTLAND INTL (PDX)
RNAV (GPS) Y RWY 10R