


WAAS CH 93801 W18A	APP CRS 182°	Rwy Ldg TDZE Apt Elev	7152 1908 1919
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 18
SAN ANGELO RGNL/MATHIS FLD (SJT)

RNP APCH - GPS.	MISSED APPROACH: Climb to 4400 direct HUMUG and on track 232° to HEXPE and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C or above 54°C. Circling NA for Cat E west of Rwy 18-36.	

ATIS 128.45 319.0	SAN ANGELO APP CON ★ 125.35 354.1	MATHIS TOWER ★ 118.3(CTAF) 284.7	GND CON 121.9 348.6	UNICOM 122.95
-----------------------------	---	--	-------------------------------	-------------------------



4400	HUMUG	tr 232°	HEXPE	HONOB	7 NM Holding Pattern
*LNAV only	ZOXUP 2.2 NM to RWY 18	ZODEN	3500	182°	002° 8000 4100
	*1.2 NM to RWY 18		*2640	3500	GP 3.00° TCH 45
	1.2 NM	1 NM	2.7 NM	5.9 NM	
CATEGORY	A	B	C	D	E
LPV DA		2158-3/4	250 (300-3/4)		
LNAV/VNAV DA		2246-1	338 (400-1)		
LNAV MDA	2340-1	432 (500-1)	2340-1 1/8	432 (500-1 1/8)	
CIRCLING	2360-1 441 (500-1)	2380-1 461 (500-1)	2500-1 1/2 581 (600-1 1/2)	2700-2 1/2 781 (800-2 1/2)	2700-2 3/4 781 (800-2 3/4)

