

WAAS CH 77927 W12A	APP CRS 121°	Rwy Ldg TDZE 230 Apt Elev 261
--	------------------------	---

RNAV (GPS) RWY 12


SANTA MARIA PUB/CAPT G ALLAN HANCOCK FLD (SMX)

⚠ Circling Rwy 2 NA at night. Baro-VNAV and VDP NA when using San Luis Obispo altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 42°C (107°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use San Luis Obispo altimeter setting and increase LPV DA to 489 feet; increase LNAV/VNAV DA to 622 feet and all visibilities to RVR 3500; increase all MDAs 60 feet and LNAV visibility Cat C/D to RVR 5500. For inop MALSR, increase LNAV Cat C/D visibility to 1½ mile. # RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using Vandenberg altimeter setting.


MALSR

MISSED APPROACH:
Climb to 800 then
climbing left turn to
5000 direct MQO
VORTAC and hold.

ATIS 121.15	SANTA BARBARA APP CON★ 124.15 327.8	SANTA MARIA TOWER★ 118.3 (CTAF) 239.25	GND CON 121.9	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------



4 NM Holding Pattern		WINCH		DEMFA		800		5000		MQO	
3300		301°		121°		121°		2000		*1.3 NM to RW12	
GP 3.00° TCH 55		2000		8.5 NM		4.2 NM		1.3 NM		*LNAV only	
CATEGORY	A	B	C	D							
LPV DA#	430/24 200 (200-½)										
LNAV/VNAV DA	563/32 333 (400-⅝)										
LNAV MDA	680/24 450 (500-½)		680/50 450 (500-1)								
CIRCLING	860-1 599 (600-1)		1000-1 739 (800-1)		1420-3 1159 (1200-3)		1540-3 1279 (1300-3)				



SW-3, 02 OCT 2025 to 30 OCT 2025

SW-3, 02 OCT 2025 to 30 OCT 2025