

ATIS
124.175 283.0
CLNC DEL
296.75
GND CON
121.85 278.95
MOFFETT TOWER★
119.55 (CTAF) 259.65
NORCAL DEP CON
120.1 290.25

TOP ALTITUDE:
ASSIGNED BY ATC



MOFFETT
Chan 123
NUQ 
(117.6)

HOOKS
6000

NOTE: TACAN required.

6000
*4100
13.6°
(31)



SALINAS
117.3 SNS 
Chan 120

TAKEOFF MINIMUMS

- Rwy 14R/L: Standard with the following minimum climb gradients:
Rwy 14R: Obstacle climb of 314’ per NM to 4900, ATC climb of 332’ per NM to 6000.
Rwy 14L: Obstacle climb of 314’ per NM to 4900, ATC climb of 328’ per NM to 6000.
Rwy 32R/L: NA, ATC.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 14L/R: Climb via NUQ R-141 to cross HOOKS/NUQ 20 DME at 6000, thence. . . .
. . . . via transition.

VALLEY TRANSITION (HOOKS2.SNS): From over HOOKS DME on SNS R-316 to SNS VORTAC.