


LOC/DME I-TUS 111.7 Chan 54	APP CRS 126°	Rwy Ldg 10996 TDZE 2599 Apt Elev 2643
---	------------------------	--

ILS or LOC RWY 12
TUCSON INTL (TUS)

RADAR or DME required. RADAR required for procedure entry at TACUB.		MALSR 	MISSED APPROACH: Climb to 4000 then climbing right turn to 6000 on heading 300° and on TUS VORTAC R-270 to MADSS/TUS 12.8 DME and hold, continue climb in-hold to 6000.
▼ For inop ALS, increase S-ILS 12 Cat E visibility to RVR 4000, ▲ S-LOC 12 Cat E visibility to 2½ SM; LEBRE fix minimums: S-LOC 12 Cat C/D/E visibility to RVR 5500. *RVR 1800 authorized with use of FD or AP or HUD to DA.			

ATIS 123.8 279.65	TUCSON APP CON 119.4 318.1	TUCSON TOWER 118.3 257.8	GND CON 120.025 348.6
-----------------------------	--------------------------------------	------------------------------------	---------------------------------



Use I-TUS DME when on the localizer course.

One Minute Holding Pattern	LIPTE I-TUS 17.5	WASON I-TUS 12.5	CALLS I-TUS 10.2	POCIB I-TUS 8.3	LEBRE I-TUS 5	HUGIK I-TUS 2.5	TUS R-270	MADSS TUS 12.8
----------------------------	------------------	------------------	------------------	-----------------	---------------	-----------------	-----------	----------------

10000
7000

←306°
126°→

GS 3.00°
TCH 55

VGSI and ILS glidepath not coincident
(VGSI Angle 3.00/TCH 73).

5700

5200

4600

3540

4000

6000

hdg 300°

5 NM

2.3 NM

1.9 NM

3.3 NM

1.9 NM

0.6

0.4

CATEGORY	A	B	C	D	E
S-ILS 12*	2799/24 200 (200-½)				
S-LOC 12	3540/40	941 (900-¾)	3540-2 941 (900-2)		
CIRCLING	3540-1¼	897 (900-1¼)	3540-2¾ 897 (900-2¾)	3640-3 997 (1000-3)	3900-3 1257 (1300-3)
LEBRE FIX MINIMUMS					
S-LOC 12	2960/24	361 (400-½)	2960/35	361 (400-¾)	
CIRCLING	3160-1 517 (600-1)	3220-1 577 (600-1)	3220-1½ 577 (600-1½)	3640-3 997 (1000-3)	3900-3 1257 (1300-3)

ELEV 2643	TDZE 2599
HIRL Rwy 12-30 MIRL Rwy 4-22 REIL Rwy 22 and 30	
FAF to MAP 5.8 NM	
Knots	60 90 120 150 180
Min:Sec	5:48 3:52 2:54 2:19 1:56

SW-4, 02 OCT 2025 to 30 OCT 2025

SW-4, 02 OCT 2025 to 30 OCT 2025