

WAAS CH 69420 W32A	APP CRS 322°	Rwy Ldg 5103 TDZE 516 Apt Elev 516
--	------------------------	---

RNAV (GPS) RWY 32
WACO RGNL (ACT)

ASR DME/DME RNP-0.3 NA. When local altimeter setting not received use Mc Gregor Exec altimeter setting and increase all DA 31 feet and all MDA 40 feet; increase LPV and LNAV/VNAV all Cats and LNAV Cats C/D visibility $\frac{1}{8}$ mile and Circling Cat D visibility $\frac{1}{4}$ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C (9°F) or above 54°C (130°F). Baro-VNAV NA when using Mc Gregor Exec altimeter setting. VDP NA with Mc Gregor Exec altimeter setting.

MISSED APPROACH:
Climb to 4000 direct
EVVIS and hold,
continue climb-in-hold
to 4000.

ATIS 123.85	WACO APP CON ★ 127.65 227.125	WACO TOWER ★ 119.3(CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------


MISSED APCH FIX

4 NM

142°

322°

EVVIS



CATEGORY	A	B	C	D
LPV DA	766- $\frac{3}{4}$	250 (300- $\frac{3}{4}$)		
LNAV/VNAV DA	773- $\frac{3}{4}$	257 (300- $\frac{3}{4}$)		
LNNAV MDA	860-1	344 (400-1)		
C CIRCLING	940-1 424 (500-1)	980-1 464 (500-1)	1020-1 $\frac{1}{2}$ 504 (600-1 $\frac{1}{2}$)	1160-2 644 (700-2)