

LOC/DME I-JAC	APP CRS	Rwy Ldg	6300
109.1	187°	TDZE	6451
Chan 28		Apt Elev	6451

ILS Y or LOC Y RWY 19

JACKSON HOLE (JAC)

RADAR required for procedure entry at MOSSS.

▼

▲

❄

Circling NA for Cats A, B and C east of Rwy 1-19. Circling NA for Cat D. For inop ALS, increase SOSUE fix minimums S-LOC 19 Cats C and D visibility to 2½ SM. For inop ALS, increase S-LOC Cat C and D visibility to 3 SM.

-21°C

MALS

⦿

⦿

MISSED APPROACH: Climb to 14000 on JAC VOR/DME R-192 to KICNE INT/JAC VOR/DME 26.6 DME and hold, continue climb-in-hold to 14000.

D-ATIS	SALT LAKE CENTER	JACKSON TOWER★	GND CON	UNICOM
120.625	133.25 285.6	118.075 (CTAF) 0	124.55	122.95

ELEV 6451	D	TDZE 6451	JAC R-192	KICNE	Use I-JAC DME when on the localizer course.	QUIRT	I-JAC 17.3	DNW 12.2	Remain within 10 NM
14000 14100 13100 11100 10200 9600 7540 7540 626 7077-1½ 7540-1¼ 1089 (1100-1¼) 7540-2½ 1089 (1100-2½) 7540-1¼ 1089 (1100-1¼) 7540-1½ 1089 (1100-1½) 7540-3 1089 (1100-3) 7300/40 849 (900-¾) 7300/55 849 (900-1) 7300-2 849 (900-2) 7300-1¼ 849 (900-1¼) 7400-2¾ 949 (1000-2¾)									
S-ILS 19									
S-LOC 19									
CIRCLING									
SOSUE FIX MINIMUMS (DME REQUIRED)									
S-LOC 19									
CIRCLING									

JACKSON, WYOMING

Amdt 1 02DEC21

43°36'N-110°44'W

ILS Y or LOC Y RWY 19

JACKSON HOLE (JAC)