

ILS or LOC RWY 4

LOC I-GLO 108.5	APCH CRS 038°	Rwy Idg 10,001 TDZE 4284 Arprt Elev 4295	[USAF]
---------------------------	-------------------------	---	--------

CANNON AFB (KCVS)

ATC RADAR or DME required. Missed approach requires use of RNAV or ATC RADAR monitoring.

***When ALS inop, increase all CAT RVR to 40 and vis to ¾ miles.**

ATIS 119.1 269.9	APP CON 118.425 352.1	TOWER 120.4 270.25	GND CON 121.9 275.8
			CLNC DEL 120.2 293.225

****When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE RVR to 60 and vis to 1½ miles.**

LOCALIZER 108.5
 I-GLO

Localizer unusable 26° right of course.

MSA CVS 2.5 NM
 6600

ELEV 4295	TDZE 4284
-----------	-----------

FAF to MAP 5.2 NM

CATEGORY	A	B	C
S-ILS 4 *	4484/24		200 (200-½)
S-LOC 4 **	4680/24 396 (400-½)	4680/35 396 (400-¾)	
CIRCLING	4840-1 545 (600-1)	4860-1½ 565 (600-1½)	5000-2¼ 705 (800-2¼) 5020-2½ 725 (800-2½)

Knots	60	90	120
Min:Sec	5:12	3:28	2:36