

LOC/DME I-EVV <u>109.9</u> Chan 36	APP CRS 221°	Rwy Ldg 8021 TDZE 422 Apt Elev 422
---	------------------------	---

ILS or LOC RWY 22
EVANSVILLE RGNL (EVV)

RADAR or DME required for procedure entry at AUGUS.


V Circling Rwy 9 NA at night. For inop ALS, increase S-LOC 22 Cats C and D visibility to 1 1/2 SM. DME minimums: For inop ALS, increase S-LOC 22 Cats C and D visibility to RVR 6000. * RVR 1800 authorized with use of FD or AP or HUD to DA.



MISSED APPROACH: Climb to 1000 then climbing right turn to 2500 direct PXV VORTAC and hold.

ATIS 120.2	EVANSVILLE APP CON ★ 124.025 290.9	EVANSVILLE TOWER ★ 118.7 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 126.6	UNICOM 122.95
---------------	---------------------------------------	--	------------------	-------------------	------------------

OWENSBORO ALT MISSED
OWB  108.65 APCH FIX
Chan 23 (Y)  310°



Procedure NA for arrival on PXV
VORTAC airway radials 355 CW 151.

POCKET CITY
113.3 PXV 
Chan 80

LOCALIZER 109.9
I-EVV
Chan 36

(IAF)
AUGUS
EVV 21.5
RADAR

JISEV INT
I-EVV 14.1

(IAF)
CUYAR INT
I-EVV 7.9
PXV 20.1

WV 3.5

Remain
within 10 NM

GS 3.00°
TCL 50

CATEGORY	A	B	C	D
S-ILS 22*	622/24		200 (200-½)	
S-LOC 22	1060/24	638 (700-½)	1060-1¾	638 (700-1¾)
CIRCLING	1060-1	638 (700-1)	1060-1¾ 638 (700-1¾)	1060-2 638 (700-2)
ZAGAK FIX MINIMUMS (DME REQUIRED)				
S-LOC 22	840/24	418 (500-½)	840/40	418 (500-¾)
CIRCLING	920-1 498 (500-1)	1040-1 618 (700-1)	1040-1¾ 618 (700-1¾)	1040-2 618 (700-2)

ELEV 422 **D** TDZE 422

221°

8021 X 150

TWR

A

B

C

D

E

F

G

H

I

J

K

L

M

N

O

P

Q

R

S

T

U

V

W

X

Y

Z

HIRL Rwys 4-22 and 18-36
REIL Rwys 4, 18, and 36
MIRL Rwy 9-27

FAF to MAP 6.4 NM

	60	90	120	150	180
Knots	6:24	4:16	3:12	2:34	2:08