

WAAS
CH **50421**
W18A

APP CRS
184°

Rwy Ldg
TDZE **396**
Apt Elev **422**

RNAV (GPS) RWY 18



EVANSVILLE RGNL (E.V.V.)

ASR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Circling Rwy 9 NA at night. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 2500 direct ADABN and hold.

ATIS 120.2	EVANSVILLE APP CON ★ 124.025 290.9	EVANSVILLE TOWER ★ 118.7 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 126.6	UNICOM 122.95
----------------------	--	--	-------------------------	--------------------------	-------------------------



2500	ADABN	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 49).		4 NM Holding Pattern
*LNAV only		MUSSL 1.9 NM to RW18	CUDAA	HEMEE
RW18		*1.1 NM to RW18	*1060	2000
1.1		0.8	3 NM	6.4 NM
CATEGORY	A	B	C	D
LPV DA	596-¾ 200 (200-¾)			
LNAV/VNAV DA	931-1¾ 535 (600-1¾)			
LNAV MDA	880-1	484 (500-1)	880-1⅔	484 (500-1⅔)
CIRCLING	920-1 498 (500-1)	1040-1 618 (700-1)	1040-1¾ 618 (700-1¾)	1040-2 618 (700-2)