HOOKZ FIVE DEPARTURE (RNAV)

TOP ALTITUDE:
(JETS) 6000
(PROPS) ASSIGNED BY ATC

RALEIGH DEP CON
125.3 353.675
D-ATIS
123.8
CLNC DEL
120.1
CPDLC
GND CON
121.9 348.6
RALEIGH TOWER
127.45 257.8

TAKEOFF MINIMUMS
Rwys 5L/R: Standard.
Rwy 14: Standard with minimum climb of 310′ per NM to 1000.
Rwy 23L: Standard with minimum climb of 250′ per NM to 2300.
Rwy 23R: Standard with minimum climb of 240′ per NM to 2100.
Rwy 32: 300-1.



NOTE: RNAV 1.
NOTE: DME/DME/IRU or GPS required.
NOTE: RADAR required.
NOTE: If unable to accept climb rate, advise ATC on initial contact.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 5L/R, 14, 23L/R, 32: Climb on assigned heading for RADAR vectors to cross FITON at or above 2500, thence. . . .

. . . .on track 197° to HOOKZ. Turbojets maintain 6000, propellers maintain altitude assigned by ATC. Expect clearance to filed altitude within ten minutes after departure.

DAWTS TRANSITION (HOOKZ5.DAWTS)

NOTE: Chart not to scale.

SE-2, 02 OCT 2025 to 30 OCT 2025