

ILS or LOC RWY 5

LOC I-FRC 110.3	APCH CRS 051°	Rwy Idg 13,899 TDZE 2462 Arpt Elev 2462	[USAF]
---------------------------	-------------------------	--	--------

FAIRCHILD AFB (KSKA)

DME or RADAR rqr'd for LOC. RADAR rqr'd for KNOCK holding.

ATIS 257.625	SPOKANE APP CON 123.75 282.25 (208° - 028°) 133.35 263.0 (029° - 207°)
------------------------	--

TOWER 120.35 233.7	GND CON 123.6 275.8
------------------------------	-------------------------------

* When ALS inop, increase RVR to 40, vis to ¾ mile.
 When TDZL/CL lights inop, increase RVR to 24; RVR 18 still authorized with use of FD or AP or HUD to DA.

** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1 ½ miles.

*** Circling S of Rwy 5-23 NA.

EMERG SAFE ALT 100 NM 10,900	ELEV 2462 TDZE 2462
------------------------------	-----------------------------------

KNOCK SKA 14	CATET SKA 14	PAIGE SKA 5.4	7000 SKA R-047	FANOT SKA 2
7000	Intcp Lczzr	4000	4000	4000
5000	5000	4000	4000	4000
050°	050°	051°	051°	051°
GS 3.00°	TCH 58	4.2 NM	0.5 NM	

ELEV 2462 TDZE 2462	2569 2583 2643 2685
-----------------------------------	------------------------------

CATEGORY	A	B	C	D	E
S-ILS 5 *	2662/18 200 (200-½)				
S-LOC 5 **	2960/24 498 (500-½)		2960/50 498 (500-1)		
*** CIRCLING	2960-1 498 (500-1)		3040-1½ 578 (600-1½)	3040-2 578 (600-2)	3600-3 1138 (1200-3)

FAF to MAP 4.2 NM					
Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:22